

1. VESSEL DESCRIPTION		
1.1	Date updated:	May 05, 2020
1.2	Vessel's name (IMO number):	Ahmet Telli (9035292)
1.3	Vessel's previous name(s) and date(s) of change:	MEDKEM ONE – SEP 25, 2014 RITA – FEB 25, 2014
1.4	Date delivered / Builder (where built):	May 2,1994 / Cantieri Navale Mario Morini, ANCONA
1.5	Flag / Port of Registry:	TURKEY/ISTANBUL
1.6	Call sign / MMSI:	TCA3356/ 271044013
1.7	Vessel's contact details (satcom/fax/email etc.):	427101642@inmc.eik.com MTahmettelli@gmail.com
1.8	Type of vessel (as described in Form A or Form B Q1.11 of the IOPPC):	Oil-Chemical Tanker
1.9	Type of hull:	Double Hull
Classification		
1.10	Classification society:	Registro Italiano Navale
1.11	Class notation:	*100-A-1.1-Nav II; Cst (oil) ESP double hull; Cst (chem) ESP IAP-IAQ1-NAU; P; PMS; VCS
1.12	Is the vessel subject to any conditions of class, class extensions, outstanding memorandums or class recommendations? If yes, give details:	No
1.13	If classification society changed, name of previous and date of change:	N/A
1.14	IMO type, if applicable:	II
1.15	Does the vessel have ice class? If yes, state what level:	No
1.16	Date / place of last dry-dock:	May 11, 2017 / Tuzla
1.17	Date next dry dock due / next annual survey due:	Aug 11,2020 Aug 19,2020
1.18	Date of last special survey / next special survey due:	May 11,2017 May 19,2022
1.19	If ship has Condition Assessment Program (CAP), what is the latest overall rating:	No
1.20	Does the vessel have a statement of compliance issued under the provisions of the Condition Assessment Scheme (CAS): If yes, what is the expiry date?	No
Dimensions		
1.21	Length overall (LOA):	114.87 m
1.22	Length between perpendiculars (LBP):	104.06 m
1.23	Extreme breadth (Beam):	16.00 m
1.24	Moulded depth:	7.68 m
1.25	Keel to masthead (KTM)/ Keel to masthead (KTM) in collapsed condition, if applicable:	31.70 m N/A
1.26	Bow to center manifold (BCM) / Stern to center manifold (SCM):	51.52 m 63.35 m
1.27	Distance bridge front to center of manifold:	53.68 m
1.28	Parallel body distances	Lightship Normal Ballast Summer Dwt
	Forward to mid-point manifold:	22.00 m 26.00 m 31.00 m
	Aft to mid-point manifold:	31.00 m 29.00 m 34.00 m
	Parallel body length:	53.00 m 55.00 m 65.00 m
1.29	FWA/TPC at summer draft:	132 mm 15.81 MT
1.30	Constant (excluding fresh water):	N/A
1.31	What is the company guidelines for Under Keel Clearance (UKC) for this vessel?	10% of max draft plus squat effect, min 500 mm in any case during sailing Min 300 mm for berthing
1.32	What is the max height of mast above waterline (air draft)	Full Mast Collapsed Mast
	Lightship:	29.10 m N/A
	Normal ballast:	27.80 m N/A
	At loaded summer deadweight:	25.60 m N/A

Tonnages			
1.33	Net Tonnage:	1,704	
1.34	Gross Tonnage / Reduced Gross Tonnage (if applicable):	4,065	N/A
1.35	Suez Canal Tonnage - Gross (SCGT) / Net (SCNT):	4,050	1704
1.36	Panama Canal Net Tonnage (PCNT):	N/A	
Ownership and Operation			
1.37	Registered owner - Full style:	Gemiciler Denizcilik San. Ve Tic. Ltd. Sti	
1.38	Technical operator - Full style:	Gemiciler Denizcilik San. Ve Tic. Ltd. Sti	
1.39	Commercial operator - Full style:	Gemiciler Denizcilik San. Ve Tic. Ltd. Sti	
1.40	Disponent owner - Full style:	N/A	

2.	CERTIFICATION	Issued	Last Annual	Expires
2.1	Safety Equipment Certificate (SEC):	May 12, 2017	July 05, 2019	May 19, 2022
2.2	Safety Radio Certificate (SRC):	May 12, 2017	July 05, 2019	May 19, 2022
2.3	Safety Construction Certificate (SCC):	May 12, 2017	July 05, 2019	May 19, 2022
2.4	International Loadline Certificate (ILC):	Jul 4, 2017	July 05, 2019	May 19, 2022
2.5	International Oil Pollution Prevention Certificate (IOPPC):	Jul 4, 2017	July 05, 2019	May 19, 2022
2.6	ISM Safety Management Certificate (SMC):	Aug 16, 2016		Aug 6, 2021
2.7	Document of Compliance (DOC):	Dec 7, 2018	Mar 11, 2020	Dec 14, 2023
2.8	USCG Certificate of Compliance (COC):			
2.9	Civil Liability Convention (CLC) 1992 Certificate:	Feb 13, 2020		Feb 20, 2021
2.10	Civil Liability for Bunker Oil Pollution Damage Convention (CLBC) Certificate:	Feb 13, 2020		Feb 20, 2021
2.11	Ship Sanitation Control (SSCC)/Ship Sanitation Control	Nov 06, 2019		May 05, 2020
2.12	U.S. Certificate of Financial Responsibility (COFR):			
2.13	Certificate of Class (COC):	Jul 4, 2017	July 05, 2019	May 19, 2022
2.14	International Sewage Pollution Prevention Certificate (ISPPC):	Jul 4, 2017		May 19, 2022
2.15	Certificate of Fitness (COF):	Jul 4, 2017	July 05, 2019	May 19, 2022
2.16	International Energy Efficiency Certificate (IEEC):	Mar 11, 2015		
2.17	International Ship Security Certificate (ISSC):	Mar 14, 2018		Apr 9, 2020
2.18	International Air Pollution Prevention Certificate (IAPPC):	Jul 4, 2017	July 05, 2019	May 19, 2022
2.19	Maritime Labour Certificate (MLC):	Sept 21, 2016	Mar 07, 2018	Apr 9, 2020

Documentation			
2.20	Owner warrant that vessel is member of ITOPIF and will remain so for the entire duration of this voyage/contract:		Yes
2.21	Does vessel have in place a Drug and Alcohol Policy complying with OCIMF guidelines		Yes
2.22	Is the ITF Special Agreement on board (if applicable)?		No
2.23	ITF Blue Card expiry date:		No

3. CREW			
3.1	Nationality of Master:	Turkish	
3.2	Number and Nationality of Officers:	6xTurkish	
3.3	Number and Nationality of Crew:	10xTurkish	
3.4	What is the common working language onboard:	Turkish	
3.5	Do officers speak and understand English?	Yes	
3.6	If Officers/Crew employed by a Manning Agency - Full style:	No	

4. FOR USA CALLS			
4.1	Has the vessel Operator submitted a Vessel Spill Response Plan to the US Coast Guard	Nil	
4.2	Qualified individual (QI) - Full style:	Nil	
4.3	Oil Spill Response Organization (OSRO) - Full style:	Nil	

5. CARGO AND BALLAST HANDLING			
Double Hull Vessels			
5.1	Is vessel fitted with centerline bulkhead in all cargo tanks? If Yes, solid or perforated:	No.	

Loadline Information					
5.2	Loadline	Freeboard	Draft	Deadweight	Displacement
	Summer:	1.585 m	6.09 m	6,025 MT	8,423 MT
	Winter:	1.712 m	5.963 m	5,852 MT	8,226 MT
	Tropical:	1,458 m	6.217 m	6,258 MT	8,632 MT
	Lightship:	5.075 m	2.60 m	0 MT	3,230 MT
	Normal Ballast Condition:	3.775 m	3.90 m	2,281 MT	4,655 MT
5.3	Does vessel have multiple SDWT? If yes, please provide all assigned loadlines:			No	
Cargo Tank Capacities					
5.4	Number of cargo tanks and total cubic capacity (98%):			18	5,979 m3
5.5	Capacity (98%) of each natural segregation with double valve (specify tanks):			1. 623.127 m3 (1 Port / Stb) 2. 695.808 m3 (2 Port /Stb) 3. 658.989 m3 (3 Port / Stb) 4. 663.282 m3 (4 Port / Stb) 5. 663.282 m3 (5 Port / Stb) 6. 663.282 m3 (6 Port / Stb) 7. 662.282 m3 (7 Port / Stb) 8. 668.282 m3 (8 Port / Stb) 9. 681.170 m3 (9 Port / Stb)	
5.6	Number of slop tanks and total cubic capacity (98%):			2	60.78 m3
5.7	Specify segregations which slops tanks belong to and their capacity with double valve:			Two deck tanks	
5.8	Residual/Retention oil tank(s) capacity (98%), if applicable:			N/A	
5.9	Does vessel have Segregated Ballast Tanks (SBT) or Clean Ballast Tanks (CBT):			SBT	
SBT Vessels					
5.10	What is total SBT capacity and percentage of SDWT vessel can maintain?			2,281.60 m3	39 %
5.11	Does vessel meet the requirements of MARPOL Annex I Reg 18.2:			Yes	
Cargo Handling and Pumping Systems					
5.12	How many grades/products can vessel load/discharge with double valve segregation:			18	
5.13	Are there any cargo tank filling restrictions? If yes, specify number of slack tanks, max s.g., ullage restrictions etc.:			NO	
5.14	Pumps	No.	Type	Capacity	At What Head (sg=1.0)
	Cargo Pumps:	18	CENTRIFUGAL	175 m3	100 mlc
		2	CENTRIFUGAL	20 m3	70 mlc
	Cargo Eductors:				
	Stripping:				
	Ballast Pumps:	2	CENTRIFUGAL	300 m3	30 mlc
5.15	Max loading rate for homogenous cargo per manifold connection:			250 m3/h	
5.16	Max loading rate for homogenous cargo loaded simultaneously through all manifolds:			600 m3/h	
5.17	How many cargo pumps can be run simultaneously at full capacity:			4	
Cargo Control Room					
5.18	Is ship fitted with a Cargo Control Room (CCR)?			Yes	
5.19	Can tank innage / ullage be read from the CCR?			Yes	
Gauging and Sampling					
5.20	Can cargo be transferred under closed loading conditions in accordance with ISGOTT 11.1.6.6?			Yes	
5.21	What type of fixed closed tank gauging system is fitted:			Tank Radar	
5.22	Number of portable gauging units (example- MMC) on board:			Hermetic UTI	
5.23	Are overfill (high) alarms fitted? If Yes, indicate whether to all tanks or partial:			Yes, All Cargo and Slop Tanks	
5.24	Are cargo tanks fitted with multipoint gauging? If yes, specify type and locations:			N/A	
5.25	Is gauging system certified and calibrated? If no, specify which ones are not calibrated:			Certified and calibrated	
Vapor Emission Control System (VECS)					
5.26	Is a Vapour Emission Control System (VECS) fitted?			Yes	
5.27	Number/size of VECS manifolds (per side):			2	100 mm
5.28	Number / size / type of VECS reducers:				
Venting					
5.29	State what type of venting system is fitted:			High speed PV valves	

Cargo Manifolds and Reducers						
5.30	Does vessel comply with the latest edition of the OCIMF 'Recommendations for Oil Tanker Manifolds and Associated Equipment'?			No		
5.31	Total number / size of cargo manifold connections on each side:			18 x 150mm		
5.32	What type of valves are fitted at manifold:			Butterfly valve		
5.33	What is the material/rating of the manifold:			Stainless Steel		
5.34	Does the vessel have a Common Line Manifold connection? If yes,			Yes		
5.35	Distance between cargo manifold centers:			820 mm		
5.36	Distance ships rail to manifold:			3,000 mm		
5.37	Distance manifold to ships side:			3,000 mm		
5.38	Top of rail to center of manifold:			2,000 mm		
5.39	Distance main deck to center of manifold:			2,550 mm		
5.40	Spill tank grating to center of manifold:			700 mm		
5.41	Manifold height above the waterline in normal ballast / at SDWT			6.325 m	4.135 m	
5.42	Number / size / type of reducers:			100 mm to 150 mm, 3 pcs 75 mm to 150 mm, 1pcs 150 mm to 200 mm, 3pcs 150 mm to 300 mm, 2pcs 250 mm to 300 mm, 1pcs DIN		
5.43	Is vessel fitted with a stern manifold? If yes, state size:			Yes, 2x 150 mm		
Heating						
5.44	Cargo / slop tanks fitted with a cargo heating system?		Type	Coiled	Material	
	Cargo Tanks:		Coils with pressurized hot water	Yes	Stainless Steel	
	Slop Tanks:		N/A	N/A	N/A	
5.45	Maximum temperature cargo can be loaded / maintained:			70 Deg Celsius	60 Deg Celsius	
5.46	Minimum temperature cargo can be loaded / maintained:			-	-	
Coating / Anodes						
5.47	Tank Coating	Coated	Typ	To What Extent	Anodes	
	Cargo tanks:	No	Stainless Steel	Whole Tank	No	
	Ballast tanks:	Yes	HC	Whole Tank	No	
	Slop tanks:	No	Stainless Steel	Whole Tank	No	
6. INERT GAS AND CRUDE OIL WASHING						
6.1	Is a Crude Oil Washing (COW) installation fitted / operational?			No		
6.2	Is an Inert Gas System (IGS) fitted / operational?			Yes		
6.3	Is IGS supplied by flue gas, inert gas (IG) generator and/or nitrogen:			Nitrogen Generator		
7. MOORING						
7.1	Wires (on drums)	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	-	-	-	-	-
	Main deck fwd:	-	-	-	-	-
	Main deck aft:	-	-	-	-	-
	Poop deck:	-	-	-	-	-
7.2	Wire tails	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	-	-	-	-	-
	Main deck fwd:	-	-	-	-	-
	Main deck aft:	-	-	-	-	-
	Poop deck:	-	-	-	-	-
7.3	Ropes (on drums)	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	2	44 mm	PP/PE bi-constituent fiber	220 m	32.70 MT
		2	40 mm		220m	35.00 MT
	Main deck fwd:	-	-	-	-	-
	Main deck aft:	-	-	-	-	-
	Poop Deck:	2	44 mm	PP/PE bi-constituent fiber	220 m	32.70 MT
2		40 mm	220m		35.00 MT	

7.4	Other lines	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	2	44 mm	Polypropylene / Polyester	220 m	32.70 MT
	Main deck fwd:	-	-	-	-	-
	Main deck aft:	1	48 mm	Polypropylene / Polyester	200 m	41 MT
	Poop deck:	1 1	44 mm 40 mm	PP/PE bi-constituent fiber	220 m 220m	32.70 MT 35.00 MT
7.5	Winches	No.	No. Drums	Motive Power	Brake Capacity	Type of Brake
	Forecastle:	2	Double	Hand Driven	25 MT	Manual
	Main deck fwd:	-	-	-	-	-
	Main deck aft:	-	-	-	-	-
	Poop deck:	2	Double	Hand Driven	25 MT	Manual
7.6	Bitts, closed chocks/fairleads	No. Bitts		SWL Bitts	No. Closed Chocks	SWL Closed Chocks
	Forecastle:	4		45 MT	-	-
	Main deck fwd:	-		-	-	-
	Main deck aft:	-		-	-	-
	Poop deck:	4		45 MT	-	-
Anchors/Emergency Towing System						
7.7	Number of shackles on port / starboard cable:				10/10	
7.8	Type / SWL of Emergency Towing system forward:				N/A	N/A
7.9	Type / SWL of Emergency Towing system aft:				N/A	N/A
Escort Tug						
7.10	What is size / SWL of closed chock and/or fairleads of enclosed type on stern:				325x230	45 MT
7.11	What is SWL of bollard on poop deck suitable for escort tug:				45 MT	
Bow/Stern Thruster						
7.12	What is brake horse power of bow thruster (if fitted):				500 BHP	
7.13	What is brake horse power of stern thruster (if fitted):				N/A	
Single Point Mooring (SPM) Equipment						
7.14	Does the vessel meet the recommendations in the latest edition of OCIMF 'Recommendations for Equipment Employed in the Bow Mooring of Conventional Tankers at Single Point Moorings (SPM)'?				NO	
7.15	If fitted, how many chain stoppers:				N/A	
7.16	State type / SWL of chain stopper(s):				N/A	N/A
7.17	What is the maximum size chain diameter the bow stopper(s) can handle:				N/A	
7.18	Distance between the bow fairlead and chain stopper/bracket:				N/A	
7.19	Is bow chock and/or fairlead of enclosed type of OCIMF recommended size (600mm x 450mm)? If not, give details of size:				N/A	
Lifting Equipment						
7.20	Derrick / Crane description (Number, SWL and location):				1x4 MT, Center cargo manifold area 1x2MT, Aft manifold area	
7.21	What is maximum outreach of cranes / derricks outboard of the ship's side:				11 m / 3m	
Ship To Ship Transfer (STS) / Helicopter Operations						
7.22	Does vessel comply with recommendations contained in OCIMF/ICS Ship To Ship Transfer Guide (Petroleum, Chemicals or Liquefied Gas, as applicable)?				Yes	
7.23	Can the ship comply with the ICS Helicopter Guidelines? If Yes, state whether winching or landing area provided and diameter of the circle provided:				No	

8.	MISCELLANEOUS		
Engine			
8.1	Speed		Maximum Economic
	Ballast speed:	12,5	11
	Laden speed:	12,5	11
8.2	What type of fuel is used for main propulsion / generating plant:	MGO	MGO
8.3	Type / Capacity of bunker tanks:	280 CuM IFO 58 CuM MGO	
8.4	Is vessel fitted with fixed or controllable pitch propeller(s):	Controllable pitch	
8.5	Engines	No	Capacity Make/Type
	Main engine:	1	2945 kW OY Wartsila AB/SR32
	Aux engine:	3	580 kW Wartsila/VD 25 V12
	Power packs:	4	255 kW Framo Frank Mohn/4xa4355
	Boilers:	1	1163 kW Wiesloch/12-V2-50
		1	698 kW Wiesloch/WA 625/50
		1	2325 kW Wiesloch/25-V2-50
Emissions			
8.6	Main engine IMO NOx Emission standard:	N/A	
8.4	Energy Efficiency Design Index (EEDI) rating number:	N/A	
Insurance			
8.8	P & I Club – Full Style:	The West of England Ship Owners Mutual Insurance Association, Luxembourg	
8.9	P & I Club pollution liability coverage / expiration date:	1,000,000,000 USD	Feb 20, 2021
8.10	Hull & Machinery insured by – Full Style:	Turk P&I	
8.11	Hull & Machinery insured value / expiration date:	4,250,000 USD	Apr 4, 2020
Recent Operational History			
8.12	Date and place of last Port State Control inspection:	01.12.2019 Port Said (Med MOU) 21.01.2020 Temryuk (Paris MOU) 28.03.2019 Odessa (Black Sea MOU)	
8.13	Any outstanding deficiencies as reported by any Port State Control? If yes, provide details:	Nil	
8.14	Has vessel been involved in a pollution, grounding, serious casualty or collision incident during the past 12 months? If yes, full description:	No	
8.15	Last three cargoes / charterers / voyages (Last / 2nd Last / 3rd Last):	Pls contact manager for details	
8.16	Date/place of last STS operation:	Pls contact manager for details	
Vetting			
8.17	Date of last SIRE inspection	Nil	
8.18	Date of last CDI inspection:	Nil	
8.19	Recent Oil company inspections/screenings (To the best of owners knowledge and without guarantee of acceptance for future business)*: <i>* "Approvals" are not given by Oil Majors and ships are accepted for the voyage on a case by case basis</i>	Nil	
Additional Information			
8.20	Additional information relating to features of the ship or operational characteristics:	Nil	